Proxima Pro AV 9300 Projector
Technical and Functional Specifications

Computer Compatibility	• Sun, SGI, IBM, HP, DEC, and X-terminals graphics modes up to 135 MHz • IBM PC, PS/2, Pentium, and compatibles • Apple Macintosh, Power Macintosh and PowerBook
Video Compatibility	• NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
Input Sources	• 2 computer input channels (optional connector modules available): Channel 1: (5) BNC (R, G, B, H, V) Channel 2: (1) HD15 • Each channel includes: RCA type stereo audio (R, L-mono), mouse control port, USB port • 2 video input channels: 3 BNC (for component, composite) 1 mini DIN 4-pin (for S-Video) 1 RCA type audio (R, L-mono)
Output Sources:	• 1 monitor output HD15 + RCA type audio (R, L-mono) (optional connector modules available) • 1 video output: 3 BNC (for component, composite) 1 mini DIN 4-pin (for S-Video) 1 RCA type audio (R, L-mono)
Control Input Sources	• RS232C (DB9)
H-Sync Range	• 15-81 kHz
V-Sync Range	• 50-100 Hz
Brightness	• 1600 ANSI lumens (typical)
Brightness Uniformity	• 85% typical
Contrast Ratio	• 100:1 ANSI; 250:1 full-on, full-off
Display Technology/No. of Colors	• 1.8" polysilicon LCD / 16.7 million colors
Resolution	• XGA (1024 x 768)
Resolutions Supported	• VGA (640x480, Fit-to-View®) SVGA (800x600, Fit-to-View) XGA (1024x768) SXGA, (1280x1024, Fit-to-View), wide format (16:9 aspect) capable
Image Diagonal (Std Lens)	• 2.5 ft. to 50 ft. (0.8 m to 15.2 m)
Projection Lens	• Power zoom and focus. 1.6:1 ratio, F2.6 ~3.5, focal length 67~107mm (long and wide lens options)
Projection Distance (Std Lens)	• 3.6 ft. to 70.8 ft. (1.1 m to 21.6 m)
Lens Shift	• Power lens shift +12 to -12° (keystone corrected)
Lamp (Life)	• 400 watt metal halide (1,000 hours)
Audio	• Two 3-watt stereo speakers
Remote Control	• Wireless IR with mouse control Wired projector (w/o mouse control) via mini-jack
Approvals	• FCC Class A, UL, cUL, CE
Power Consumption	• 630 watts
Power Requirements	• 90-264 volts (110~120/200~240V + 10%) at 50/60 Hz
Operating Temperature (Sea Level)	• 41-95° F (5-35° C)
Weight	• 37.4 lb. (17.0 kg)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.

Dimensions	• 15.4 in. (W) x 22.9 in. (L) x 9.2 in. (H) 23.3 cm (W) x 58.2 cm (L) x 39.0 cm (H)
Projection Method	• front/rear, desktop/ceiling
On-screen Menu Languages	• English, German, French, Italian, Spanish
Audible Noise	• < 42db
Dot Clock	• Up to 135 MHz
Horizontal Resolution	• 800 video lines
Warranty	• Two years on parts and labor (excluding lamp)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.